

DATASHEET



6820039 EASHOOK OPEN

DETAILS

- Material(s): aluminum
- Certification(s): CE EN 362, EAC



SPECIFICATIONS

References	M043AA00	M043AA01
Locking system	Automatic	Automatic
Color(s)	Grey/Yellow	Black
Weight	160 g	160 g
Major axis strength	25 kN	25 kN
Open gate strength	10 kN	10 kN
Gate opening	25 mm	25 mm
Guarantee	3 years	3 years
Packing	1	1

6820039 EASHOOK OPEN

DESCRIPTION

- Designed for use at the ends of ABSORBICA-Y, PROGRESS or PROGRESS ADJUST-type double lanyards and the GRILLON-type work positioning lanyard
- Removable carabiner:
 - gated connection point allows for direct attachment of the carabiner to the lanyards. If the lanyard is damaged, the connector can thus be reused
 - special connection point helps keep the carabiner loaded on the major axis
- Facilitates handling when passing intermediate anchors:
 - ergonomic shape for excellent grip
 - automatic double-action locking system is easy to use
 - wide opening for easy connection of the carabiner
 - Keylock system to avoid any involuntary snagging of the carabiner
- H cross-section:
 - ensures an improved strength-to-weight ratio
 - protects markings from abrasion
- Also available in black

DATASHEET

