

TECHNICAL DATASHEET

FM4 FULL FACE MASK



DESCRIPTION

FM4 is a full facemask providing the highest levels of respiratory protection. A novel hose connection brings the hose up over the wearer's shoulder, keeping the work area clear.

The mask has an ultra comfortable silicone face seal and offers a virtually unrestricted field of vision.

- Non dermatitic silicone construction minimises risk of skin irritation
- Reverted edge face seal ensuring good fit and increased safety
- Provides impact protection, allowing use in environments where both respiratory and face protection is required
- High efficiency speech diaphragm allows wearer to communicate clearly
- Three sizes available

FM4 is approved for respiratory protection when used with SPIRIT, Tornado and Proflow powered air systems.

APPROVALS

CE certified to EN12942 TM3 and AS/NZS1716-P3.

TECHNICAL SPECIFICATIONS

Respiratory Protection:	Proflow Tornado SPIRIT	EN 12942 TM3 and AS/NZS 1716-P3 EN 12942 TM3 and AS/NZS 1716-P3 EN 12942 TM3 and AS/NZS 1716-P3
Assigned Protection Factor (Nominal):	Proflow Tornado SPIRIT	40 (2000) 40 (2000) 40 (2000)
Minimum design flow rate:	Proflow Tornado SPIRIT	120 l/min 140 l/min 160 l/min
Effective weight of mask on head:	630g	
Noise level:	<65 dB(A)	
Operating Temperature Limits:	-10°C to +50°C	
Face Seal Material	Non dermatitic Silicone	

For hose selection see [Hose/Headtop/Blower Compatibility Matrix](#)