



# — PRODUCT DATA SHEET

## P17



P17

## SPECIFICATIONS

## TIMELINE

Earliest launch of sales	02-10-2017
Global launch date	02-10-2017
Shipping date	31-08-2017
Order date	17-07-2017

## TECHNICAL DATA

Length defocused [mm]	306
Length focused [mm]	325
Head diameter [mm]	53
Tube diameter [mm]	40
Weight incl. batteries [g]	785
Weight without batteries [g]	378
Focus function	Yes
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Plastic lense (PMMA)
Cartridge	No

## POWER SUPPLY

Power source type	Battery
Battery quantity	3
Battery type	Alkaline
Battery description	Mono (D) 1.5V
Rechargeable	No
Energy modes	Energy Saving

## FURTHER SPECIFICATIONS

IP class	IPX4
Drop test (drop height) [m]	1
Working temperature range [°C]	-20 to +40

## LIGHT FUNCTIONS

Low Power, Power, Boost

## LIGHT SOURCE

Amount LEDs	1
LED type	Xtreme LED
Color	White
Color temperature [K]	6000 to 8000
Color rendering index (CRI)	65

## LIGHT VALUES

	Boost	Power	Mid Power	Low Power
Light output <sup>1</sup> [lm]	1000	400	100	100
Beam distance <sup>1</sup> [m]	450	300	150	150
Run time <sup>1</sup> [h]	15	50	300	300

## SWITCH

Front Switch

## TECHNOLOGIES

Advanced Focus System<sup>3</sup>, Rapid Focus

**YEAR**  
**WARRANTY<sup>4</sup>**

## PACKAGING AND LOGISTICS



Exemplary Packaging Illustration



Exemplary Packaging Illustration

## PACKAGING INFORMATION

Type of packaging	Gift Box
Scope of delivery	1 set of batteries, Intelligent clip
Item No.	500903
Customs tariff number	85131000

## SINGLE PACKAGE

Dimensions W x H x D [cm]	36.5 x 5.9 x 12.4
Gross weight [g]	1143
GTIN-13	4058205009935

## EXPORT CARTON

Unit	12
Dimensions W x D x H [cm]	39 x 26.5 x 40
Gross weight [kg]	14.79
GTIN-13	4058205010924

## PACKAGING INFORMATION

Type of packaging	Blister
Scope of delivery	1 set of batteries, Intelligent clip
Item No.	500904
Customs tariff number	85131000

## SINGLE PACKAGE

Dimensions W x H x D [cm]	17 x 44 x 5.9
Gross weight [g]	1021.5
GTIN-13	4058205009942

## INNER CARTON

Unit	6
Dimensions W x D x H [cm]	45.5 x 38.5 x 19.5
Gross weight [g]	7275
GTIN-13	4058205010931

## EXPORT CARTON

Unit	12
Dimensions W x D x H [cm]	47.5 x 40.5 x 43.5
Gross weight [kg]	16.06
GTIN-13	4058205010948

P17

## ACCESORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME
Fastenings / Brackets	0311	Tripod Adaptor Type B
Fastenings / Brackets	0319	Intelligent Clip Type E
Color filter / Signal caps	0042	Signal Cone 53mm
Roll Protections	0321	Roll Protection Ring 39 mm

## MARKETING

## KEY SELLING POINTS

- Optimized operating time – Up to 300 hours<sup>1</sup> in the lowest setting
- Very good lighting performance – Up to 450 meters<sup>1</sup> beam distance with up to 1,000 lumen<sup>1</sup> of luminous flux
- Simple operation – 3 light functions, 1 front switch
- Battery-operated – Three D alkaline batteries (mono, LR20, 1,5 V) are used
- For a long lifetime – Robust metal housing and high-quality gold contacts

## PRODUCT COPY

**The Ledlenser P17**  
**And it shines and shines and shines.**

Design and technology have never come together so well. The Ledlenser's P17 casing is black and due its coating has an elegant and velvety appearance. The rippled surface means it sits particularly well in your hand, and what's on the inside also proves that the flashlight has a lot going for it. With a battery life of up to 300 hours<sup>1</sup> on the lowest setting, it continues to shine when other lights have long gone out.

## SERIES COPY

**The Ledlenser P-Series**  
**Minimalist design, maximum performance.**

The sturdy flashlights of the Ledlenser P-Series offer top performance in stylish designs. While externally they only have the bare essentials, they are packed full of useful technical functions, like the Rapid Focus and the Advanced Focus System. This makes them to indispensable little helpers for everyday life: For example, for renovating, tidying and rearranging, taking the dog out, during blackouts, and much more.

## FOOTNOTES

The information pertaining to package contents, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change package contents, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurements according to ANSI FL1 on the respective setting. Average values, in some cases, deviations by +/- 15 % may occur due to technical reasons. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting and to battery duration (hours/hrs/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light has different energy modes, measurement is based on "energy saving mode."

3) EP Patent 1880139, US Patent 7,461,960

4) Warranty period of five years from the date of purchase, seven years if the product is registered online on our website. The warranty is valid worldwide and legal warranty rights also apply. It covers defects in materials and workmanship. For the proper functioning of rechargeable batteries a different warranty period of 24 months applies. Excluded from this warranty are the products of the "Solidline" series, Ledlenser K1 and Ledlenser K2. The warranty does not apply to Defects in batteries, holsters, pouches, remote switches, color filters, imprints or surface coatings. The guarantor is Zweibrüder Optoelectronics GmbH & Co. KG, Kronenstr. 5 - 7, 42699 Solingen, Germany. More information: [ledlenser.com/warranty](http://ledlenser.com/warranty)