



Chemical protection

ULTRANEO 382

Frequent contact | ultra-comfort wear



CHEMICAL PROTECTION
TYPE A



2121X



TYPE A
ALMNST




EN ISO 374-5



X1XXXX



0334



DEXTERITY
EN 420:
5/5

Maximum comfort and chemical protection

(SPECIFIC ADVANTAGES)

Thermal protection

- Added comfort and thermal insulation, due to the cotton-knit lining

Comfort

- Extremely supple, due to the unique Mapa multi-layer process

Productivity

- Embossed texture for better grip on wet objects

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Additional benefits

- Available in vending machine packaging

(INDUSTRIES)

- Automotive/mechanical industry
- Chemical industry
- Other industries

(APPLICATIONS)

- Chemical product blending
- Handling drums of chemical products
- Manipulating valves
- Laboratory tests
- Machine maintenance
- Engine part assembly
- Surface treatment



Chemical protection

ULTRANEO 382

Frequent contact | ultra-comfort wear

(LEGENDS)

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

2	1	2	1	X	P
0-4	0-5	0-4	0-4	A-F	Impact protection (optional)
					Cut resistance according to ISO 13997
					Puncture resistance
					Tear resistance
					Blade cut resistance
					Abrasion resistance

EN407



THERMAL RISKS (HEAT AND FIRE)

PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4
					Resistance to large quantities of molten metal
					Small splashes of molten metal
					Radiant heat resistant
					Convective heat resistance
					Contact heat resistance
					Limited flame spread

EN ISO 374-1



CHEMICAL RISKS

A: Methanol
L: Sulphuric acid 96%
M: Nitric acid 65%
N: Acetic acid 99%
S: Hydrofluoric acid 40%
T: Formaldehyde 37%

TYPE A

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

(PRODUCT DETAILS)

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Polychloroprene
Cuff characteristic	Feston Cuff
Colours	Blue
Length (cm)	36
Thickness (mm)	0.95
Size	6 7 8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.5E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	5.2E+10 Ω

(LOGISTIC DETAILS)

Packaging

12 pairs/bag
72 pairs/carton

(LEGISLATION)

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1646 updated 02-07/10/2021
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificate: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France