



A tough, mid-cut safety shoe with highest protection level (S3) and BOA[®] Fit System built for heavy work.

 HEAVY DUTY 1278

EN ISO 20345:2011 S3, SRC, CI, HRO, HI ASTM F2413-18 M/I/C SD 35 PR



[Learn more](#)

A tough, mid-cut safety shoe with highest protection level (S3) and BOA[®] Fit System built for heavy work. The PU-coated leather and microfibre upper gives excellent foot protection and additional ankle support. The oil and heat-resistant nitrile outer sole gives excellent grip, and JALAS[®] Composite Toe Cap, nail protection in steel and double impact protection zones in PORON[®] XRD[®] mean safer workdays.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Pull loops
- Water repellent
- Heat-resistant outsole
- Oil-resistant outsole
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- BOA[®] Fit System
- Bellows tongue
- TPU heel support
- Padded shaft edge in memory foam
- Ankle support
- Ergonomically shaped



PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Steel

FITTING Regular

COLLECTION Heavy Duty

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Composite

LINING MATERIAL Polyester, polyamide

INSOLE FX2 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black, Blue

NET WEIGHT, (SIZE 42) 1,4 kg

COMPLIANCE



Cat. II

EN ISO 20345:2011
S3, SRC, CI, HRO, HI



ASTM F2413-18
M/I/C
SD 35 PR

TP TC 019:2011



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Oil-resistant outsole



ProNose toe reinforcement



Composite toecap



Ergothan Shock Absorption System



ESD



Nail protection in steel



Heat-resistant outsole



Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3.5	4	1278-35	198106024133
36	3	4	5	1278-36	198106024126
37	4	5	6	1278-37	198106024119
38	5	5.5	6.5	1278-38	198106024102
39	6	6.5	7.5	1278-39	198106024096
40	6.5	7.5	8.5	1278-40	198106024089
41	7	8	9	1278-41	198106024072
42	8	9	10	1278-42	198106024065
43	9	9.5	11	1278-43	198106024058
44	10	10.5	11.5	1278-44	198106024041
45	10.5	11	12.5	1278-45	198106024034
46	11	12	13	1278-46	198106024027
47	12	13	14	1278-47	198106024010
48	13	13.5	14.5	1278-48	198106024003

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com