

6803021 CARABINER OK TRIACT-LOCK

DESCRIPTION

- Symmetrical oval shape allows optimal loading of devices with a wide cross-section, such as pulleys, rope clamps and mobile fall arresters
- Aluminum carabiner whose light weight reduces the weight of equipment the worker at height needs to carry
- May be used with a CAPTIV positioning bar to favor loading of the carabiner along the major axis, to keep it integrated with the device, and to limit the risk of it flipping
- Easier handling:
 - fluid interior design limits the risk of having a catch point and facilitates rotation of the carabiner
 - Keylock system to avoid any involuntary snagging of the carabiner
- H cross-section:
 - ensures an optimal strength/weight ratio
 - protects markings from abrasion



- Available in three different locking systems:
 - TRIACT-LOCK: automatic locking with triple-action gate opening
 - BALL-LOCK: automatic locking with triple-action gate opening, with lock indicator
 - SCREW-LOCK: the manual screw-lock with red band provides a visual warning when the carabiner is unlocked
- Also available in black (TRIACT-LOCK and SCREW-LOCK)

SPECIFICATIONS

- Material(s): aluminum
- Certification(s): CE EN 362, EAC

REFERENCES

References	M33A TL	M33A BL	M33A SL	M33A TLN	M33A SLN
Weight	75 g	75 g	70 g	75 g	70 g
Locking system	TRIACT-LOCK	BALL-LOCK	SCREW-LOCK	TRIACT-LOCK	SCREW-LOCK
Color(s)	gray	gray	gray	black	black
Major axis strength	25 kN	25 kN	25 kN	25 kN	25 kN
Minor axis strength	8 kN	8 kN	8 kN	8 kN	8 kN
Open gate strength	7 kN	7 kN	7 kN	7 kN	7 kN
Gate opening	22 mm	23 mm	22 mm	22 mm	22 mm
Guarantee	3 years	3 years	3 years	3 years	3 years
Packing	1	1	1	1	1