

PERCAP BANDED EARPLUGS

OVERVIEW	
Product Type	Hearing Protection
Range	Earplugs
Line	Temple Earplugs
Product Use	Temple Earplug, Foldable
Brand	Howard Leight by Honeywell
Industry	Industry • Administration • Agriculture • Army - Defence • ATEX Environment • Automotive and Part Manufacturer • Aviation • Building and Construction • Catering • Chemical Industries • Energy or Electricity • Fire Protection Brigades • Foundry • Glass Industries • Green Spaces • Homeland Defense • Industrial Cleaning • Iron and Steel Industry • Laboratory • Logistics • Maintenance • Medical and Pharmaceutical • Metal Steel • Mining and Quarrying • Offshore • Paper Industries • Petro-Chemical • Printing Industries • Services • Ship Building • Telecoms • Textile Industries • Transportation • Utilities • Water Treatment • Welding • Wood Industries



FEATURES

Semi-aural protection, super soft pods rest outside the ear canal opening. Multiple position wear: over-the-head, under the- chin or behind-the-neck provides flexibility in wear. Compact, folding design easy to store in pocket. Ideal for workers who are exposed to intermittent noise.

BENEFITS

For workers who are exposed to intermittent levels of noise, Howard Leight's PerCap banded earplugs offer an alternative to earplugs and earmuffs. From its compact design to semi-aural protection, PerCap offers reliable protection from noise with ear pods that rest outside of the ear canal opening. PerCap can be worn in three positions and folds down for pocket-sized storage, ideal for supervisors and other workers who are in and out of noisy areas, and need easy access to hearing protection.

STORAGE INFORMATION

All earplugs should be stored before and between usages in a way that protects them from dirt, grease, and other contaminants.

CARE INSTRUCTIONS

Ear pods should be cleaned by removing all ear wax and contaminants prior to re-insertion. Soiled pods may be wiped clean with a moist cloth before every use. (Recommended every 2-4 weeks.)

TECHNICAL DESCRIPTION			
SNR (DB)	30	Size	Fits All
H (DB)	32	Color	CMYK
M (DB)	27	Shape/ Corded	Oval pad/No
L (DB)	25	Weight (G)	0.70

ATTENUATION DATA ACCORDING TO EN 352-2: 2020								
Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	29.2	25.8	28.4	29.9	31.1	36.1	42.4	44.5
Standard Deviation (dB)	4.3	4.3	5.2	5.7	5.5	4.2	3.3	4.8
Assumed Protection (dB)	24.9	20.8	23.2	24.3	25.6	31.9	39.1	39.7

CERTIFICATIONS	
EU Category PPE	3
Quality Assurance	ISO 9001 / 2000
EU Certification	2777/24340-01/E00-00

ADDITIONAL INFORMATION	
User Manual	Instruction Manual - Percap (Global)

SKU	DESCRIPTION (EN)
1005952	1005980 Howard Leight Percap Foldable Band
1005980	1005980 Howard Leight Percap Replacement Pods x10p

For more information

sps.honeywell.com

Honeywell Safety Products UK LTD

Honeywell House, Skimped Hill Lane,
Bracknell, Berkshire RG12 1EB
United Kingdom
Phone: +44 (0) 1256 274938
Email: info-uk.hsp@honeywell.com
www.honeywell.com

HPPE Hearing Percap Banded | Technical Data | 08/23
© 2023 Honeywell International Inc.

Honeywell
HOWARD
LEIGHT