

WHE00115

EN



TECHNICAL DETAILS


MATERIAL

 EXTERNAL SHELL:
HD Polypropylene

STANDARD

EN 12492

 Protection against top impacts and
penetration in conformity with
EN 397

 Clause 5.1.1 Protection against
top impacts
Clause 5.1.2 Protection against
penetration
Clause 5.1.3 Flame resistance
EN 397 additional tests:
-30°C / LD / MM

 WHE00115-201
WHITE

 WHE00115-202
YELLOW

 WHE00115-203
ORANGE

 WHE00115-204
RED

 WHE00115-209
BLACK

SIZE

 Universal-adjustable
from 52 to 63 cm

WEIGHT

460 g


TEMPERATURE OF USE

-30°C / +35°C


CATEGORY

II

TECHNOLOGIES


POLYPROPYLENE HD EXTERNAL SHELL

 Lightweight external shell with exponential better performance.
Excels in impact absorption, especially at lower temperatures
(-30°C). Resists yellowing and degradation.

HD EPS INTERNAL SHELL

 Inner shell composed of high-density foam for all-around impact
energy absorption and improved comfort.

CLICK-IN SYSTEM

 Enhanced padding attachment system that quickly secures into
place and allows for easy replacement, and removal. Patented
system improves padding durability.

2DRY LINER

 A quick-drying fabric with moisture-wicking technology that
accelerates the dispersion of sweat to the surface of the helmet
padding for a drier, more comfortable wear.

ERGO FIT SYSTEM

 Helmet size adjusting system that allows for an easy and secure
fit by turning the large diameter dial. The system moves up and
down to adapt to a range of head shapes. The ergonomically
shaped wings cradle the back of the neck for added comfort.

ADVANCED LITE CHINSTRAP

 Chinstrap with 5 adjustment points for a personalized fit.
Accommodates wider head sizes and adapts to earmuff use.
Color-coded fasteners indicate EN standard compliance rating.

LATERAL ADJUSTMENT DIVIDER

 Side regulator point on chinstrap for adjustment and positioning
for a more tailored fit.

RING TO HOOK

 Chinstrap loop that enables the wearer to securely attach the
helmet to a harness or other items.

EARMUFF ATTACHMENT SLOTS

 Helmet designed with standard 30mm EURO slots for attaching
KASK hearing protection earmuffs.

VENTILATION CHANNELS

 Designed with 14 air intakes shaped to prevent debris entry and
internal channels for enhanced breathability and wearer comfort.

EARPLUG HOOKS

Lamp clip feature that holds corded earplugs.


FRONTAL ACCESSORY SLOT

 Front attachment point for advanced customization and easy
integration of accessories such as badge holders and headlamps.
Includes cap cover for debris protection.

TECHNOLOGIES

NECK PROTECTOR SLOT

3 rear helmet slots for mounting KASK Neck Protection products.



EASY CLICK SYSTEM

Helmet designed with integrated slots for easy mounting of KASK eye and face protection accessories. Easy Click Visor Adapters required.



REPLACEABLE LAMP CLIPS

Helmet designed with 4 removable nylon lamp attachment clips. Compatible with KASK headlamps and other headlamps with elastic bands.

PERFORMANCES

Protection against top impacts	K	5 kg from 2 m 100 J
Protection against side, front and rear impacts	K	5 kg from 0,5 m 25 J
Protection against the penetration of objects	K	3 kg from 1 m 30 J
Chinstrap release > 50 kg	K	
Retention system effectiveness	K	

Ventilation	K	
Lower temperature resistance test	K	T= -30°C
Protection against side deformation	K	LD
Protection against molten metal splashes	K	MM

K EN 12492 standard requirements **Y** EN 397 additional requirements

ADDITIONAL INFORMATION

SHELF LIFE

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

3
YEARS
GUARANTEE

10
YEARS
SHELF LIFE

GUARANTEE

3 years starting from the date of purchase.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

STORAGE

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES



WVI00007
ZEN VISOR



WVI00022-500
ZEN FACE SHIELD



WVI00008
ZEN FULL FACE VISOR



WVI00009/10
ZEN MM/PM VISOR



WHP00004/5/6
EARMUFFS



WLA00001/2/3
HEADLAMPS



WPA00007
WINTER PADDING



WAC00013/25
NECK SHADE



WAC00032/33
NECK SHIELD RW



WAC00036-37
SUN SHIELD

DISCOVER MORE



SCAN FOR
COMPLETE
COLLECTION