

NLG Large D Ring Tool Tether

101362



NLG Large D Ring Tool Tether

Product code: 101362

PRODUCT BRIEF / 101362

Attach the Large D Ring Tool Tether with Tether Tape to create an instant attachment point on any large hand tool.

NLG D-Ring Tether form part of NLG's unique Instant Tether System for stopping dropped objects and is well established as the preferred option for workers at height. They can be retro-fitted to almost any tool avoiding the unnecessary expense of buying new tools or the associated downtime of sending tools off site to be adapted for tethering.

When used with Tether Tape, the NLG D-Ring Tether Points provide a solution to a multitude of tools commonly used at work – spanners, podgers, hammers etc – in fact, almost any hand tool up to a maximum weight limit of 3kg.

As an integral part of a tool kit, the NLG D-Ring Tether and Tether Tape provide a versatile and quick solution to keep tools safe when working at height and means that no worker will have to waste time again on site through a lack of correctly tethered tools.

INSTRUCTIONS

- 1/ Select the correct D Ring Tether for you tool.
- 2/ Cut a length of Tether Tape long enough to wrap around the tool at least 8 times. Remove the plastic backing.
- 3/ Check the tool is clean and locate the D Ring Tether, ensuring that the label is facing up. Wrap the Tether Tape around the D Ring Tether, leaving the webbing catch exposed.
- 4/ Ensure that the Tether Tape is firmly stretched during application. The self-fusing technology is activated when stretched between 5-10% and causes it to fuse permanently.
- 5/ Test the tether point before putting the tool into use.

VIDEO GUIDE



Watch online:
neverletgo.com/tool-tether-guide

Specification

- Super strong welded D Ring
- Extended product life with high strength, wear resistant webbing
- Extra deep catch design for ultimate security
- Faster visual inspections with contrast stitching
- Works with Tether Tape
- Unique serial number for easy identification and tracking
- CE marked
- Dynamic load tested and third party certified [2:1 safety factor]
- Dimensions: 100mm x 25mm
- Max Load: 3KG [6.6lbs]

MAX LOAD [SWL]

3KG / 6.6LBS

SERIAL NUMBERED

Makes the management of inspection routines and reports easy and traceable

PRODUCT DATA

Weight: 22 Grams
EAN [GTIN-13]: 5060572180048
HTS Code: 6307.90.9899



Third party
tested and
certified

See the
Test Certificate
on page 5





Breathe Safety Testing Laboratory

UKAS Testing No 8856 | Accredited to ISO/IEC17025/2005

**DROP TEST CERTIFICATE****IMAGE***After tests have been conducted***DATE**

June 2016

PRODUCT

D Ring Tether Large

REFERENCE

101362

MAX LOAD

3 KG

SAFETY FACTOR / TEST LOAD

2:1 / 6 KG

DYNAMIC DROP TEST RESULTS

	FACTOR 0	FACTOR 1	FACTOR 2
1	PASS	PASS	PASS
2	PASS	PASS	PASS
3	PASS	PASS	PASS

TECHNICIAN COMMENTS AND OBSERVATIONS

Stitching Intact.
 No elongation on webbing.
 Stainless Steel D Ring - no signs of visual wear or stress.

SIGNATURE

Gary Paterson
 Senior Lab Technician

United Kingdom Accreditation Service**ACCREDITATION CERTIFICATE**

TESTING LABORATORY
 No. 8856
 Breathe Safety Limited

Please note that the results included in this report relate only to the specific equipment samples tested. This is for the purpose of Type Approval of Equipment under the PPE Directive. For more detail refer to the full Accredited Laboratory Policy. This report may not be reproduced without authorisation from the laboratory. Any deviations from specific test methods are described in the relevant section of the report.

- Fully Equipped Laboratory for CE Type Approval Testing
- Product Trial testing for specific tests
- CE Technical File review and consultancy advice
- CE Certification facilitation through a partner Notified Body

0844 915 1111

17 Whittle Road, Ferndown Industrial Estate, Ferndown, Dorset BH21 7RL, UK



NLG Large D Ring Tool Tether

Product code: 101362

View online

neverletgo.com/large-d-ring-tool-tether/

Get all the Product Briefs

neverletgo.com

Tool Tethering Experts

+44 [0]330 016 0030

neverletgo.com