

6820184 PETZL AXIS

SPECIFICATIONS

- Diameter: 11 mm
- Material(s): polyester, nylon
- Certification(s): CE EN 1891 type A, EAC, NFPA 1983 Technical Use
- Weight per meter: 82 g
- Strength with sewn termination: 22 kN
- Impact force (factor 0,3): 5,2 kN
- Number of factor 1 falls: 12
- Construction: 32 carrier
- Percentage of sheath: 41 %
- Static elongation: 3 %



REFERENCES

References	R074BA00	R074BA01	R074BA02	R074BA03	R074BA04	R074BA05
Length	10 cm	20 cm	30 cm	40 cm	50 cm	60 cm
Color(s)	white	white	white	white	white	white
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years
Packing	1	1	1	1	1	1

6820184 PETZL AXIS

DESCRIPTION

- Standard diameter ensures a good grip for easier handling
- Consistent performance over time:
 - EverFlex construction with nylon core and polyester sheath, with specific weave
 - this construction ensures great flexibility over time, under any conditions (water, dust, mud...), which allows it to maintain excellent handling and optimal functioning with devices
- Comes with sewn termination that allows it to meet the EN 353-2 standard for use with an ASAP mobile fall arrester, or to be part of a rescue kit that includes an I'D S descender. This termination has a protective sheath that keeps the carabiner in position and facilitates handling
- Standard lengths: 10, 20, 30, 40, 50 and 60 m
- Customization by request:
 - option of ordering a rope of a specified length
 - addition of a sewn termination on one end