

## 6802140 GRILLON

### SPECIFICATIONS

- Certification(s): CE EN 358, EAC



### REFERENCES

References	L52A 002	L52A 003	L52A 004	L42A 005
<b>Length</b>	2 m	3 m	4 m	5 m
<b>Weight</b>	435 g	515 g	595 g	675 g
<b>Guarantee</b>	3 years	3 years	3 years	3 years
<b>Packing</b>	1	1	1	1

## 6802140 GRILLON

### DESCRIPTION

- Lanyard with fine adjustment system for precise work positioning
- Can be used in two ways:
  - in double mode on the side attachment points of the harness, to distribute the weight on the belt (user has weight on his feet): length is adjusted by pressing on the pivoting cam)
  - in single mode on the harness ventral attachment point, to distribute weight between the waistbelt and the leg loops (user is suspended): length is adjusted by operating the handle while holding the free end of the lanyard
- Removable protective sheath protects the rope from abrasive surfaces and allows smooth rope glide.
- The protection can be removed when the lanyard is used in single mode, to bring the user closer to the anchor.
- Available in four lengths: 2, 3, 4 and 5 m
- NOTE: GRILLON lanyards can also be used to create adjustable anchors or horizontal lifelines. Please see specific versions of GRILLON lanyards for these uses.