



STAY

SUPPORT LANYARD 9654

- ANSI and CE certified without adjustment
- Strong against sharpe edges

Support lanyard without adjustment.

SEGMENTS

- ✓ Tower climber
- ✓ Offshore
- ✓ Wind energy

ARTICLES

012204060	Cresto, Stay 9654 1,0 m
012204062	Cresto, Stay 9654 1,2 m

OVERVIEW

Stay is a support lanyard with materials of the highest quality. The line is certified for 140 kg and approved according to both CE and ANSI.

SPECIFICATION

PRODUCT PROPERTIES

Attaching connector 1	ANSI certified trippellock carabiner in aluminum
Attaching connector 2	Big ANSI certified aluminum hook with 64 mm opening
Gate strength (kN)	16.0
Gate opening (mm)	64.0
Adjustable under load	No
Energy absorber	No
Fall indicator	No
Maximum number of users	1
Minimum load (kg)	140.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Minimum breaking strength - MBS (kN)	25.0
Material	Polyamide
Rope	12 mm kern mantle rope in polyamide by the brand Patron from Teufelberger

CLASSIFICATION

EN-standard	EN 354 : 2010, EN 795 : 2012
Notified body	1019, VVUU, a.S., Pikartaske 1337/7 716 07 Ostrava - Radvanice Czech Republic
Other standards	ANSI Z359.4-2013

ANNUAL INSPECTION

Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	Czech (CS), Danish (DA), Dutch (NL), English (EN), Estonian (ET), Finnish (FI), French (FR), German (DE), Norwegian (NO), Slovak (SK), Slovenian (SL), Spanish (ES), Swedish (SV)

CRESTO GROUP

Lägatan 3
302 63 Halmstad
Sverige

T. +46 35 710 75 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE

IMAGES

