

Product Brief

NLG Heavy Duty Bungee Tool Lanyard

101373

NLG

NLG Heavy Duty Bungee Tool Lanyard

Product code: 101373

PRODUCT BRIEF / 101373

The Heavy Duty Bungee Lanyard utilises advanced components to deliver unrivalled performance for heavy tools in the most severe environments.

The NLG Heavy Duty Bungee Lanyard is designed to handle the heavier tools and plant that other lanyards struggle with - right up to a maximum of 18kg weight. It has become established as the tool lanyard of choice in some of the harshest working environments known on this planet.

It features a custom developed, abrasion-resistant webbing with a Dyneema® loop one end for connecting directly to a tether point, or through a captive handle or hole on any tool and a twist lock carabiner on the other end, that is still easy to use whilst wearing gloves, qualify the Heavy Duty Bungee Lanyard as the ultimate tool tethering lanyard.

Specification

- Automatic Twistlock carabiner for superior performance and security
- Extra high strength webbing delivers ultimate peace of mind
- Heavy duty wear protector sleeve provides an additional layer of structural protection
- Powerful cinching loop constructed from the world's strongest fibre, Dyneema®
- Faster visual inspections with heavy-duty contrast stitching
- Clever contrast wear indicators ensure early warning of any structural damage
- Unique serial number for easy identification and tracking
- CE marked
- Dynamic load tested and third party certified [2:1 safety factor]
- Dimensions: Extends 80cm to 130cm
- Max Load: 18KG [39.6lbs]

MAX LOAD (SWL)

18KG / 39.6LBS

SERIAL NUMBERED

Makes the management of inspection routines and reports easy and traceable

PRODUCT DATA

Weight: 175 Grams
 EAN [GTIN-13]: 5060572180253
 HTS Code: 5609.00.4000



Third party
tested and
certified

See the
Test Certificate
on page 5





Breathe Safety Testing Laboratory

UKAS Testing No 8856 | Accredited to ISO/IEC17025/2005

**DROP TEST CERTIFICATE****IMAGE***After tests have been conducted***DATE**

June 2016

PRODUCT

Heavy Duty Bungee Lanyard

REFERENCE

101373

MAX LOAD

18 KG

SAFETY FACTOR / TEST LOAD

2:1 / 36 KG

DYNAMIC DROP TEST RESULTS

	FACTOR 0	FACTOR 1	FACTOR 2
1	PASS	PASS	PASS
2	PASS	PASS	PASS
3	PASS	PASS	PASS

TECHNICIAN COMMENTS AND OBSERVATIONS

No Elongation on the webbing
 Elasticity retained at original level
 No signs of stress on the webbing
 Stitching intact
 Hardware shows no sign of stress

SIGNATURE

Gary Paterson
Senior Lab Technician

United Kingdom Accreditation ServiceACCREDITATION CERTIFICATETESTING LABORATORY
No. 8856

Breathe Safety Limited

Please note that the results included in this report relate only to the specific equipment samples tested. This is for the purpose of Type Approval of Equipment under the PPE Directive. For more detail refer to the full Accredited Laboratory Policy. This report may not be reproduced without authorisation from the laboratory. Any deviations from specific test methods are described in the relevant section of the report.

- Fully Equipped Laboratory for CE Type Approval Testing
- Product Trial testing for specific tests
- CE Technical File review and consultancy advice
- CE Certification facilitation through a partner Notified Body

0844 915 1111

17 Whittle Road, Ferndown Industrial Estate, Ferndown, Dorset BH21 7RL, UK



NLG Heavy Duty Bungee Tool Lanyard

Product code: 101373

View online
[neverletgo.com/
heavy-duty-bungee-tool-lanyard/](http://neverletgo.com/heavy-duty-bungee-tool-lanyard/)

Get all the Product Briefs
neverletgo.com

Tool Tethering Experts
+44 [0]330 016 0030
neverletgo.com