



**PRODUCT NUMBER: 1005325**  
**ME86 - Manyard Shock absorbing Lanyard - 2m - ML00+ML04**

Complete 2m with 1 galvanised connector and 1 snap hook 63mm.



**Overview**

**Reference Number**  
1005325

**Product Type**  
Fall Protection

**Range**  
Shock Absorbing Lanyards

**Brand**  
Miller by Honeywell

**Industry**

- Industry
- Building and Construction

**Product Use**  
 2m Shock absorbing Lanyard - complete with 1 screwgate karabiner (ML00) & Automatic Snap hook, with TEFLON finish  
 Added elasticity 32%  
 Integrated shock absorber  
 Highly resistant external webbing, Teflon finish  
 Warning flag  
 1 Screw karabiner and 1 Automatic Scaff hook  
 Security Clip

**Features & Benefits**

**Feature**  
 A unique stretchable design. A safety clip that straps on to the harness to hold the Manyard when not in use. Special woven shock-absorbing inner core. Heavy tubular outer jacket. Unique warning flag which provides visual proof that a lanyard has been involved in a fall and should be removed from service. Reliable visual inspection: the integral res core becomes visible if the outer jacket is damaged or worn. The TEFLON hi-tech protective finish on the outer tubular jacket prolongs the service life of the Manyard.

**Benefit**  
 Lightweight and easy to use, the elasticated manyard is ideal for maintenance on cranes or granties. When contracted the elasticated shock-absorbing lanyard reduces the risk of tripping or snagging. The unique woven shock-absorbing material reduces fall arrest forces.

**Technical Description**

**Length**  
2m

**Weight**

0.985 Kg

**Breaking Strength**

> 15 KN

**Operating Temperature**

-30°C to +50°C

**Webbing**

**Webbing Raw Material**

Polyamide

**Webbing Breaking Strength**

> 2200 daN

**Connector**

**Connector Type**

TypeCS20

**Connector Raw Material**

Raw MaterialZinc-plated steel

**Connector Opening**

Opening18 mm

**Connector Breaking Strength**

Breaking Strength> 2500 daN

**Connector Standard**

StandardEN 362

**Connector**

**Connector Type**

TypeSnap hook

**Connector Raw Material**

Raw MaterialWhite chromate steel

**Connector Opening**

Opening65 mm

**Connector Breaking Strength**

Breaking Strength> 2200 daN

**Connector Standard**

StandardEN 362

**Energy Absorber**

**Energy Absorber Raw Material**

Polyester fibers

**Energy Absorber Breaking Strength**

> 500 daN

**Complementary Information**

Elasticity 32,8 % Length Folded 1.35m External highly resistant webbing Polyamide webbing 45mm - green Teflon finish

Breaking strength: > 2200 daN

**Certifications**

 **E.C. Declaration of Conformity**

**EC Category PPE**

3

**Quality Assurance**

ISO 9001 / 2000

**EC Certificate Number**

333

**EC Attestation**

 EC Attestation

**EC Attestation Number**

0082/490/160/04/01/0089 EXT N°01/10/08

## Additional Information

**User Manual**

NT90004208 IND L

**User Information Sheet**

User manual

## Packaging

**EAN Code**

7312550053256