



Strong disposable gloves that offer a higher level of protection against harmful exposures.

- Ultimate barrier significantly reduces risk of harmful exposures and rip-tear
- 2X more chemical splash protection than leading brands[†] due to breakthrough polymer bonding technique^{*}
- Highest known standard for barrier quality and consistency (Low 0.40 AQL)[‡]
- Made with TNT™ Chemical Splash Resistance Technology, for soft durable protection against a wide range of chemicals
- Silicone free design is paint and finish process friendly



Industries

- Life Sciences
- Chemical
- Automotive
- Automotive Aftermarket
- Food Processing
- Machinery and Equipment
- Maintenance

Recommended For

- Laboratory analysis
- Sample taking and processing
- Transferring liquids and solids
- Light assembly tasks
- Paint shop
- Blending, compounding materials
- Light chemical handling
- Filtration Process
- Cleaning of equipment, tables and floors
- Light duty maintenance
- Pharmaceutical manufacturing
- Chemical Splash



TECHNICAL DATA SHEET

PRODUCT INFORMATION

	93-850
Material	Nitrile
Color	Green
Glove Design	Powder-Free, Chlorinated, Silicone Free, Textured Fingers
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 9001:2008
Regulatory/Standards Compliance	ASTM D6319, Category III, EN ISO 374-5:2016, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN 421:2010, FDA21 CFR 177-2600, ISO 9001
Packaging	100 gloves per dispenser; 10 dispensers per case; 1000 gloves per case; *90 gloves per dispenser (Size XXL); *900 gloves per case (Size XXL)
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
User Needs Segment	Robust
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10), XXL (10.5 - 11)
Anti-static	Yes
Vulcanization Chemical Accelerators	<ul style="list-style-type: none"> Zinc Dibutyldithiocarbamate (ZDBC) <p><i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i></p>

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	0.40 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.19 / 7.5		ASTM D3767,EN 420
	BEFORE AGING		AFTER AGING
Ultimate Tensile Strength (MPa)	27	27	ASTM D412 & D573
Elongation at Break (%)	620	550	ASTM D412
Force at break (N)	12	12	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	93850060	93850070	93850080	93850090	93850100	93850110

Technology



Chemical Splash
Resistance Technology

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
(Malaysia) Sdn Bhd
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.