

Product leaflet

Product
Face shield

Model No.
SR 570

Ordering No.
H06-6512

Product Description

The SR 570 face shield together with the battery-powered SR 500 or SR 700 fan and approved filters are included in the Sundström fan-assisted respiratory protection device systems. The breathing hose of the face shield is to be connected to the fan, equipped with filters. The pressure generated in the face shield prevents particles and other pollutants from entering the hood.

The equipment can be used as an alternative to filter respirators in all situations for which filter respirators are recommended. This applies particularly to work that is hard, warm or of long duration.

The characteristics of the SR 570 face shield are as follows:

Protects the breathing zone and the crown of the head • Hinged visor unit • Scratch resistant and chemicals resistant PC visor • Adjustable head harness • Airflow deflector for optimal comfort • The supply air flow keeps the visor demisted • Replaceable breathing air hose • Standard fastener for hearing protection • Optional peel-offs • PC visor and visor frame protects from high speed particles 120 m/s at extremes of temperature, liquid splashes and molten metal • Equipped with an exhalation valve • Available in one size.

Technical specification


SR 570/SR 500/SR 700 EN 12941:1998 +
A2:2008

Air flow rate	175-240 l/min (SR 500) 175-225 l/min (SR 700)	≥ 120 l/min
Service temperature	-10 – +55°C, < 90 % RH	-
Storage temperature	-20 – +40°C, < 90 % RH	-
Low flow warning level	< 175 l/min	≤ 175 l/min
Weight with breathing hose	≈ 850 g	≤ 1 500 g
Impact test with 6 mm dia. steel ball against visor	120 m/s	-
Assigned Protection Factor¹	40 (TH3)	-
Nominal Protection Factor²	500 (TH3)	-
Approvals	EN 12941:1998 + A2:2008 EN 166:2001 EN 812:2012 with Bump cap	-

1) Specified in BS 4275 and applies regardless of the test results.

2) According to EN 529:2005.

- A. SR 570
C. SR 500
D. SR 700
E. Hearing protectors



Head Office

Tel: +46 10 484 87 00

Visiting address:
Stockholmsvägen 33
SE-181 33 Lidingö

Factory

Tel: +46 10 484 87 00

Visiting address:
Västergatan 4
SE-341 50 Lagan

Sundström 
www.srsafety.com