

TRACKER

HIGH PROTECTION

Ultra-comfortable and technical TRACKER provides protection from all mechanical risks and also chemical risks making it unique in the safety glasses range.

 PLATINUM



Removable foam



TRACPSI



TRACPSF



TRACPSJ



TRACWPC2



TRACWPC3



TRACWPC5



52 g

SUPPLIED WITH

Microfibre pouch
ETUIFS



OPTIONAL

Optical insert only single vision
SOSTRACKER



AVAILABLE IN
RX

+ UPPER PROTECTION

+ SIDE VENTILATION

**+ REMOVABLE FOAM REINFORCEMENT
WITH INDIRECT VENTILATION**

+ LOWER PROTECTION

+ REMOVABLE ADJUSTABLE STRAP

bolle
SAFETY

TRACKER

HIGH PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
TRACKER Temple version	 Clear	TRACPSI	2C-1,2  1 BT KN C€	 EN166 FT C€	Anti-scratch /Anti-fog (*P)
	 Smoke	TRACPSF	5-2,5  1 BT KN C€	 EN166 FT C€	Anti-scratch /Anti-fog (*P)
	 Yellow	TRACPSJ	5-1,4  1 BT KN C€	 EN166 FT C€	Anti-scratch /Anti-fog (*P)
	 Welding shade 1,7	TRACWPCC2	1,7  1 FT C€	 EN166 FT C€	Anti-scratch
	 Welding shade 3	TRACWPCC3	3  1 FT C€	 EN166 FT C€	Anti-scratch
	 Welding shade 5	TRACWPCC5	5  1 FT C€	 EN166 FT C€	Anti-scratch
TRACKER Strap version	With strap	-	-	 EN166 3 4 BT C€	-
	Kit Foam and strap	TRACKITFS	-	-	-
SOS TRACKER	Optical insert	SOSTRACKER	-	-	

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- B.** Impact à moyenne énergie, résiste à une bille de 6 mm et de 0,86 g à 120 m/s.

Others symbols:

- K.** Resistance to surface damage by fine particles (optional)
- N.** Resistance to fogging (optional)
- C€ European standard  Manufacturer name

TECHNOLOGY

PLATINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes.
In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.

4. Large dust particles > 5 microns.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY

TRACKER

HIGH PROTECTION

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC
STRAP	Nylon
FOAM	EVA

PACKAGING AND EAN13 CODE

	TRACPSI	TRACPSF	TRACPSJ	TRACWPCC2	TRACWPCC3	TRACWPCC5	TRACKITFS	SOSTRACKER
Individual plastic bag	3660740004828	3660740004835	3660740004842	3660740000400	3660740000417	3660740000424	3660740000257	3660740000028
10 safety spectacles per inner box	3660740104825	3660740104832	3660740104849	3660740100407	3660740100414	3660740100421	3660740100254	3660740100025
240 safety spectacles per outer pack	3660740204822	3660740204839	3660740204846	3660740200404	3660740200411	3660740200428	3660740200251	3660740200022



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY